

CNOGA Firmware Updater User Manual

Contents

1.	Overvie	2W	3
2.	Prerequ	isites	3
3.	User Int	terface	4
3	.1 Run	nning the CFU for the first time	4
3	.2 Upc	lating the firmware	7
	3.2.1	Connect the device	7
	3.2.2	Device Data	7
	3.2.3	Updating the firmware	8

1. Overview

The CNOGA Firmware Updater Home Edition (<u>CFU</u>) is a PC-side application that interacts with the Tensor-Tip device. It is responsible for Identification and updating the firmware of the Tensor-Tip via USB. The <u>CFU</u> upgrades the Tensor-Tip device using a CNOGA configuration loaded during the upgrade process from the Internet.

2. Prerequisites

The CFU was tested and is supported on the following platforms:

- Windows 7.
- Windows 8.1.
- Windows 10.

The CFU installer will look for those components on the PC when the installation is launched and will install the missing items before installing the CFU itself. A connection to the Internet may be required for the installation.

A standard micro USB cable will be needed for the connecting the TensorTip device to your computer.

3. User Interface


3.1 Running the <u>CFU</u> for the first time

There are two ways to start the CFU application:


- 1. Shortcut on your desktop named "TensorTip Updater"
- From the start menu as well: Start->All Programs->CNOGA Medical-> CNOGA firmware Updater Home.

Note for Windows 7 users:

Run the program in administrator mode. Right click on "CNOGA firmware Updater Home " icon and select "Run as administrator".



When running the program for the first time the <u>CFU</u> initializes the internal and will ask the user to sigh in to Cnoga.



Click "ok" to continue.

Registration process



Click "Sign In" at the upper right corner of the window.

A Window of the registration will be popup

CNoga Firmware U	pdater	
Sig	n In to CNo	oga
Use the email	you registrated wi	ith to sign in
Email		
Password		
	Sign In	
Cancel	Forgot Password	New User

Click "New User" if you didn't sing in yet.

If you have already registered, please fill in the Email and password and click "sign In" to continue and Skip to content 3.2.

Registration Details

	Registration Details
Email	
You can't leave this empty Password	
Password	
Name	
You can't leave this empty Last Name	
You can't leave this empty Country	
You can't leave this empty City	-
You can't leave this empty Street	
You can't leave this empty Zip Code	
You can't leave this empty Phone Number	
You can't leave this empty	

Fill up all the details located in the registration form all red letters are registered mandatory fields.

Click "ok" to continue.

3.2 Updating the firmware

3.2.1 Connect the device


Start the <u>CFU</u> from the start menu. The <u>CFU</u> will be loaded:

Connect the device to be upgraded. Note that the <u>CFU</u> upgrades only one device at the same time. Do not connect more than one device to the PC while the <u>CFU</u> is running. The best practice would be to disconnect all Tensor-Tip devices from the PC, start the <u>CFU</u> and connect the device to be upgraded.

3.2.2 Device Data

After connecting the Tensor-Tip device the following form will be displayed.

On the 1st connection the CNOGA Firmware Upgrader Tensor Tip driver will be install automatically



The connected device data is displayed on the upper left corner.



The CFU will display whether the current version updated.

NOTE: If a message appears "The device is up to date" means that there's no update.

If a message appears "There is newer version for your device" means that there's a new update.

3.2.3 Updating the firmware

CNoga Firmware Updater						
File Options	Help					
	Product Name:	MTX				
P the P	Serial Number:	000000145301048	$\langle \Box \rangle$			
	Hardware Version:	0.03.0.0	$\overline{}$			
· · ·	Firmware Version:	3.96.0.0				
Update						
opuate						
There is newer version for your device Update Firmware						

Start the firmware update process.

Click on the "Update Firmware" button, highlighted by a red circle, to start the firmware update process.

No Options			10-0112-0044 000
		Dears Dans	
	Product Nerrar 3114		
	Serial Number 0000004550008		
1997	Seriel Number 03343CG4158CG43		
	Herdivers Verdiere DUD1251		
	Firmane Venion 338.8.8		
Update			
There is never sortion for	A CONTRACTOR OF A CONTRACTOR OFTA CONTRACTOR O		
Local ferrines person 3.3			
Service and an over state 2.3.			
		11%	
			The second s
			14/8
🐢 e 📷	o 👩 💌 🏖 🛷		TH - P # 10 4: 164
	the second of the second se		Wax doi:

The following screen will be displayed when running:

NOTE: During the update process.

- Do not disconnect the Tensor-Tip device being updated from the PC.
- Do not connect other Tensor-Tip devices to the PC.
- Do not close the CNOGA Firmware Updater application.
- Do not restart or shutdown your PC.
- Do not press on the buttons of the device.
- Do not open the lid or insert your finger to the chamber.

Firmware update completed

When the firmware update process has completed successfully, the following screen will be displayed.

Choga Himware Updator	The second s		- a ×
File Options	Help		bi)/582@yahoo.com
		Device Store	
	Product Name: M/TX Serial Nambor: 00000143301047 Handware Vension: 0.03.0.0 Firmware Vension: 3.97.4.0		
Update			
The device is up to date.	Update Ferrivizro		
		C freqs freework lipidate Update was successful	
🧿 ၉ 📋	0 0 0		64 - •• 🖨 🗂 👀 11.07

Click "ok" and disconnect the device.

The device is ready to be used.

To update another device repeat the process 3.2.3

3.2.4 Update Frimware from file

One more option to update the device is by downloading a cfp file.

NOTE: the file will be sent from Cnoga Medical Support team.

Click "File" and Select "Update Firmware From File".

Select the file cfp and continue updating.

	Options	Help	
Update	Firmware From File	e	Ctrl+O
1: C:\\Firmware\AiO_COG_CN_3.97.5.0\CFU.cfu 2: C:\\COG_RegionalOut2Bin 3.97.5.0.cfu 3: C:\\Firmware\AiO_COG_CN_3.97.5.0\asd.cfu 4: C:\Users\alext\Desktop\AiO_COG_CN_3.97.5.0\CFU.cfu 5: C:\Users\alext\Desktop\AiO_COG_CN_3.97.5.0.cfp 6: C:\Users\alext\Desktop\PT_BINS\PT.cfu 7: C:\\Firmware\AiO_LITE_MTX_GE_1.11.3.0\CFU.cfu 8: C:\\Firmware\MTX_3.97.5.0\MCUonly.cfu			
Exit	\Firmware\MTX_3.9	m.s.o(Test.clu	Alt+F4